



**100% COPPER
WINDING MOTOR**



 **everwell®**

AIR CURTAIN



Model	Power Supply V/Ph/Hz	Air Flow m ³ /h / CFM	Air Speed HIGH m/s / ft/s	Approximate Decibel dB	Mounting Height m / ft	Net Weight kg / lb	Gross Weight kg / lb	Unit Size LxWxH mm / in	Packing Size mm / in
FM1209N-2Y-S1	115/1/60	1780 / 1047	11.0 / 36	≤45	2.3-3 7.5-9.8	12.80 / 28.22	14.30 / 31.53	900×220×195 35.4x8.7x7.7	960×280×250 37.8x11x9.8
FM1209N-2Y-S2	230/1/60								
FM1212N-2Y-S1	115/1/60	2370 / 1394		≤47		15.70 / 34.61	17.70 / 39.02	1200×220×195 47.2x8.7x7.7	1260×280×250 49.6x11x9.8
FM1212N-2Y-S2	230/1/60								
FM1215N-2Y-S1	115/1/60	2970 / 1748		≤47		19.9 / 43.87	22.40 / 49.38	1500×220×195 59.1x8.7x7.7	1560×280×250 61.4x11x9.8
FM1215N-2Y-S2	230/1/60								
FM1218N-2Y-S1	115/1/60	3560 / 2095		≤50		23.0 / 50.71	26.0 / 57.3	1800×220×195 70.9x8.7x7.7	1860×280×250 73.2x11x9.8
FM1218N-2Y-S2	230/1/60								



Metal casing, strong fire resistance, simple installation and easy cleaning.



Double air way deflector's design obtains an even air stream.



The air wheel made of high-strength fiberglass plastic material is especially suitable for the application of heavy oily smoke.



Quality motor works for 5000 hours continuously without any defects.



Multiple unit specifications: 900mm, 1200mm, 1500mm, 1800mm



Magnetic door switch + remote control included

**100% COPPER
WINDING MOTOR**

